



Barri-Ring Oval



Barri-Ring Oval: Simplified Fire-Rated Wall Protection

Barri-Ring oval is a complimentary product of the Barri-Ring with all the same great features. The oval design is meant to capture valves in which the water stops are coming out of the valve at a 45-degree angle, and to fit a wider range of plumbing valves

- **UL Tested and Listed:** Compliant with W-L-7325 for shower valve penetrations, meeting code-required equal "T" rating.
- **Versatile Compatibility:** Works with both non-metallic and metallic escutcheon plates, and fits metal and wood stud framing.
- **Robust Construction:** Minimum 2½ inch shaft wall included, tested in back-to-back configurations.
- **Quality Material:** Made of durable stainless steel, ensuring long-lasting performance.
- **Convenient Access:** Center opening allows easy access to line shut-off screws.
- **Easy Installation:** Fits into a 4½ to 5 inch hole in gypsum with **NO CAULKING REQUIRED!**
- **Specifications Available:** Find detailed specs on [Deltak SpecPoint/MasterSpec](#), [RIB SpecLink](#), [Upcodes](#), and [ARCAT](#).
- **Patent Pending:** Proudly made in the United States of America.

ANSI/UL1479 (ASTM E814)	CAN/ULC 5115
F Ratings — 1 and 2 Hr (See Items 1 and 3)	F Ratings — 1 and 2 Hr (See Items 1 and 3)
T Ratings — 1 and 2 Hr (See Items 1 and 3)	FT Ratings — 1 and 2 Hr (See Items 1 and 3)
	FH Ratings — 1 and 2 Hr (See Items 1 and 3)
	FTH Ratings — 1 and 2 Hr (See Items 1 and 3)

